



KONTAKT⁸

21

Table of Contents

1. Disclaimer	1
2. Welcome to the Kontakt Lua API Reference Manual	2
What's New in Kontakt 8.3	2
3. Introduction and Setup	3
Document Conventions	3
Basic Usage	4
Tutorials	4
Command Line and Debugging	5
VS Code Setup	5
Sublime Text Setup	6
Version History	7
API Access	7
Errors	7
Modules	7
Security	7
Available Lua Libraries	7
4. Multi	8
General Information	8
Multi Structure	8
Constants	9
max_num_multi_scripts	9
Get Property	10
get_multi_name	10
get_multi_script_name	10
get_multi_script_source	10
get_num_instruments	10
is_multi_script_bypassed	10
is_multi_script_protected	10
Set Property	11
set_multi_name	11
set_multi_script_bypassed	11
set_multi_script_name	11
set_multi_script_source	11
Modifiers	12
reset_multi	12
File I/O	13
save_multi	13
load_multi	13
5. Instrument	14
General Information	14
Instrument Structure	14
Constants	15
cc64_modes	15
instrument_purge_modes	15
max_num_instrument_aux	15
max_num_instruments	15

max_num_scripts	15
max_num_voice_groups	15
save_modes	15
voice_stealing_modes	15
Get Property	17
get_free_instrument_index	17
get_instrument_aux_level	17
get_instrument_indices	17
get_instrument_midi_channel	17
get_instrument_mute	17
get_instrument_name	17
get_instrument_options	17
get_instrument_output_channel	18
get_instrument_pan	18
get_instrument_polyphony	18
get_instrument_script_linked_filename	18
get_instrument_script_name	19
get_instrument_script_source	19
get_instrument_solo	19
get_instrument_tune	19
get_instrument_volume	19
get_voice_groups	19
is_instrument_script_bypassed	19
is_instrument_script_linked	19
is_instrument_script_protected	19
Set Property	20
reset_instrument	20
set_instrument_aux_level	20
set_instrument_midi_channel	20
set_instrument_mute	20
set_instrument_name	20
set_instrument_options	20
set_instrument_output_channel	21
set_instrument_pan	22
set_instrument_polyphony	22
set_instrument_script_bypassed	22
set_instrument_script_linked_filename	22
set_instrument_script_name	22
set_instrument_script_source	22
set_instrument_solo	22
set_instrument_tune	22
set_instrument_volume	22
set_voice_groups	23
Modifiers	24
add_instrument	24
add_instrument_bank	24
remove_instrument	24
remove_instrument_bank	24
File I/O	25
load_instrument	25
load_snapshot	25
save_instrument	25
save_snapshot	25

6. Group	26
Constants	26
group_playback_modes	26
group_start_conditions	26
group_start_operators	26
max_num_group_start_criteria	26
max_num_groups	26
voice_group_modes	26
Get Property	28
get_group_name	28
get_group_pan	28
get_group_playback_mode	28
get_group_start_options	28
get_group_tune	29
get_group_volume	29
get_num_groups	29
get_voice_group	29
Set Property	30
set_group_name	30
set_group_pan	30
set_group_playback_mode	30
set_group_start_options	30
set_group_tune	31
set_group_volume	31
set_voice_group	31
Modifiers	32
add_group	32
remove_group	32
File I/O	33
load_group	33
save_group	33
7. Zone	34
Constants	34
max_num_sample_loops	34
max_num_zones	34
sample_loop_modes	34
zone_grid_modes	34
Get Property	35
get_num_zones	35
get_sample_loop_count	35
get_sample_loop_length	35
get_sample_loop_mode	35
get_sample_loop_start	35
get_sample_loop_tune	35
get_sample_loop_xfade	35
get_zone_geometry	35
get_zone_grid_bpm	36
get_zone_grid_mode	36
get_zone_group	36
get_zone_high_key	36
get_zone_high_key_fade	36
get_zone_high_velocity	36

get_zone_high_velocity_fade	36
get_zone_low_key	36
get_zone_low_key_fade	36
get_zone_low_velocity	36
get_zone_low_velocity_fade	37
get_zone_pan	37
get_zone_root_key	37
get_zone_sample	37
get_zone_sample_channels	37
get_zone_sample_end	37
get_zone_sample_frames	37
get_zone_sample_start	37
get_zone_sample_start_mod_range	37
get_zone_tune	38
get_zone_volume	38
Set Property	39
set_sample_loop_count	39
set_sample_loop_length	39
set_sample_loop_mode	39
set_sample_loop_start	39
set_sample_loop_tune	39
set_sample_loop_xfade	39
set_zone_geometry	39
set_zone_grid	40
set_zone_group	40
set_zone_high_key	40
set_zone_high_key_fade	40
set_zone_high_velocity	40
set_zone_high_velocity_fade	40
set_zone_low_key	40
set_zone_low_key_fade	40
set_zone_low_velocity	41
set_zone_low_velocity_fade	41
set_zone_pan	41
set_zone_root_key	41
set_zone_sample	41
set_zone_sample_end	41
set_zone_sample_start	41
set_zone_sample_start_mod_range	41
set_zone_tune	41
set_zone_volume	42
Modifiers	43
add_zone	43
remove_zone	43
restore_loops_from_sample	43

8. Presets 44

Constants	44
bus_fx	44
group_fx	44
insert_fx	44
main_fx	44
output_fx	44

send_fx	44
File I/O	45
load_source_preset	45
load_fx_preset	45
load_multi_script_preset	45
load_script_preset	45
load_fx_chain_preset	45
9. Options	46
Constants	46
desktop_path	46
documents_path	46
factory_path	46
macos	46
ni_content_path	46
non_player_content_base_path	46
snapshot_path	46
windows	46
10. Utility	47
Constants	47
colored_output	47
edit_instrument	47
script_executed_from_instrument	47
script_file	47
script_path	47
version	47
Functions	48
assert_fail	48
create_resource_container	48
link_resource_container	48
get_file_info	48
instrument_purge	48
File I/O	49
ncw_decode	49
ncw_encode	49
11. Filesystem	50
API Access	50
Iterators	51
directory	51
recursive_directory	51
Path Functions	52
empty	52
extension	52
filename	52
has_parent_path	52
has_relative_path	52
has_root_directory	52
has_extension	52
has_filename	52
has_root_name	52
is_dot_dot	52

is_dot	52
join	52
has_stem	53
is_absolute	53
relative_path	53
has_root_path	53
root_name	53
root_directory	53
is_relative	53
parent_path	53
root_path	53
replace_extension	53
preferred	53
stem	53
12. Music Information Retrieval (MIR)	54
API Access	54
Pitch Detection	55
detect_pitch	55
Peak, RMS & Loudness detection	56
detect_peak	56
detect_rms	56
detect_loudness	56
Loop Detection	57
Type Detection	58
sample_type	58
detect_drum_type	58
detect_instrument_type	58
13. Version History	59
Kontakt 8.2	59
Kontakt 8.1	60
Kontakt 8	61
Kontakt 7.10.7	62
Kontakt 7.8	63

1. Disclaimer

The information in this document is subject to change without notice and does not represent a commitment on the part of Native Instruments GmbH. The software described by this document is subject to a License Agreement and may not be copied to other media. No part of this publication may be copied, reproduced or otherwise transmitted or recorded, for any purpose, without prior written permission by Native Instruments GmbH, hereinafter referred to as Native Instruments.

“Native Instruments”, “NI” and associated logos are (registered) trademarks of Native Instruments GmbH.

All other trademarks are the property of their respective owners and use of them does not imply any affiliation with or endorsement by them.

Document authored by Holger Zwar, Mario Krušelj, Yaron Eshkar, Jonas Körwer

Software version: 8.0 (9/2024)

2. Welcome to the Kontakt Lua API Reference Manual

Welcome to the Kontakt Lua API reference manual. Kontakt Lua API is the technology which enables programmatic Kontakt instrument editing and creation workflow through a straightforward imperative approach, directly running within Kontakt itself.

This resource is a reference manual that covers every function, command, constant and other elements of the Kontakt Lua API. Where applicable, it also includes examples and short code snippets that demonstrate how a given function can be used. To learn more about Kontakt, refer to the [Kontakt User Manual](#).

What's New in Kontakt 8.3

New Features

- Added support for changing `komplete_ui_module_name`, `komplete_ui_width` and `komplete_ui_height` via `set_instrument_options`. To match this, `get_instrument_options` will return the current values for these options.

Removed

- Removed `set_komplete_ui_module`
- Removed `get_komplete_ui_module`
- Removed `set_komplete_ui_size`
- Removed `get_komplete_ui_size`

3. Introduction and Setup

Document Conventions

Constants and functions in this reference document are described using the following conventions:

```
constant_name: constant_type
```

```
function_name(argument_name: argument_type, ...) -> return_type
```

Optional arguments or return values are marked by a question mark ?. If a table can be passed as an argument, or is returned by a function, its key-value pairs are described below the function.

Basic Usage

Kontakt Lua API scripts can be executed either from Kontakt's user interface, or passed as a command line argument when running Kontakt from a command line.

In Kontakt's main menu the entry "Run Lua script..." (**F11**) opens a file select dialog. In order to run the same script again, press **Ctrl+F11** (**Cmd+F11** on macOS).

Lua scripts also show up in Kontakt's Files browser and can be executed by a double-click or by dragging and dropping a script onto the rack. Drag and drop is also possible from operating system's file manager (Finder on macOS or Explorer on Windows).

Kontakt Lua API is designed to cooperate with Kontakt's rack and edit views. Running a script operates on the current state of Kontakt, without resetting it. This allows for utility scripts which can do specific tasks that can be cumbersome to do manually in the edit view. If you need to start with a clean state, simply call `Kontakt.reset_multi()`. The constants `edit_instrument` provide necessary information to retrieve the current context.

In order to start using Kontakt Lua API facilities, please enable Developer Options checkbox in Kontakt's *Options > Developer* pane.

Tutorials

Tutorial scripts demonstrating various aspects of Kontakt Lua API are available [here](#). These tutorials contain workflow examples with ample comments to get you up to speed, as well as test samples to support various mapping operations.

Command Line and Debugging

If a filename with the extension `.lua` is passed as an argument when opening Kontakt from the command line, the script is executed. The script output is directed to the terminal.

- On Windows, a terminal window will open automatically with Kontakt standalone.
- On macOS, a terminal window will only open if Kontakt is started from the package. Right-click on **Kontakt 8.app** and select *Show Package Contents*, then open **Contents/macOS/Kontakt 8**.

On both platforms, messages from Lua scripts will be visible in the terminal panel of the text editor if Kontakt was launched within the editor. KSP messages, warnings, script errors and variable watching will also be routed to this terminal. However, if Creator Tools is running, all messaging from Kontakt will be redirected to its debugger instead.

This is the recommended workflow. Follow the instructions below for your preferred text editor in order to set this up.

VS Code Setup

1. Press **Ctrl+Shift+P** (**Cmd+Shift+P** on macOS) to open the Command Palette.
2. Search for command *Tasks: Open User Tasks*, then choose **Others** from the list.
3. Paste the text below in the newly created file (replacing everything else), then save.
4. Load in VS Code the Lua file containing the script you want to execute.
5. In the main menu of VS Code, go to *Terminal > Run Task...* and select **Kontakt 8** to open the terminal along with Kontakt.

tasks.json:

```
{
  "version": "2.0.0",
  "tasks": [
    {
      "label": "Kontakt 8",
      "type": "shell",
      "command": "\"/Applications/Native Instruments/Kontakt 8/Kontakt 8.app/Contents/macOS/Kontakt 8\"",
      "windows": {
        "command": "C:\\Program Files\\Native Instruments\\Kontakt 8\\Kontakt 8.exe",
        "options": {
          "shell": {
            "executable": "cmd.exe",
            "args": ["/d", "/c"]
          }
        }
      },
      "args": ["${file}"],
      "problemMatcher": [],
      "presentation": {
        "echo": true,
        "reveal": "always",
        "focus": false,
        "panel": "shared",
        "showReuseMessage": true,
        "clear": true
      }
    }
  ]
}
```

Sublime Text Setup

1. Navigate to *Tools > Build System > New Build System...*
2. Paste the text below in the newly opened file.
3. Save this file as **Kontakt.sublime-build**.
4. Navigate to *Tools > Build System > Kontakt* to execute.

Kontakt.sublime-build (macOS):

```
{
  "shell_cmd": ["\"/Applications/Native Instruments/Kontakt 8/Kontakt 8.app/Contents/macOS/Kontakt 8\"", "$file"],
}
```

Kontakt.sublime-build (Windows):

```
{
  "cmd": ["c:\\Program Files\\Native Instruments\\Kontakt 8\\Kontakt 8.exe",
"$file"],
}
```

Note: Sublime Text does not support colored console output. Set [colored_output](#) to false in order to disable sending ANSI color codes to output. If the logger is not working, try using `cmd` instead of `shell_cmd`.

Version History

API Access

Kontakt Lua API is defined in the global table **Kontakt**, i.e. all constants and functions need to be prefixed with that name. For example:

```
Kontakt.reset_multi()

-- also works
local kt = Kontakt

kt.reset_multi()
```

Errors

All functions potentially fail and print an error message pointing to the line causing the error. The reason is usually an invalid argument. Consider using [pcall](#) in order to handle errors.

Modules

It is recommended to move reusable functionality into [Lua modules](#) and include them via the **require** keyword. Lua's **package.path** is initialized with the folder pointing to the script.

Security

Since potentially unsafe libraries e.g. [Operating System Facilities](#) are available, it is highly recommended to run scripts or include modules **from trusted parties only!**

Available Lua Libraries

- [Standard libraries](#) are documented in the Lua manual.

4. Multi

General Information

Multi Structure

The multi is the topmost hierarchy level in Kontakt. It consists of **64 instrument slots**. An instrument slot can contain a single instrument, or a single instrument bank, itself consisting of up to **128 instruments**. In Kontakt Lua API, this is represented with **instrument index**, which assumes **128** indices per instrument slot. For example, in order to reference an instrument loaded in third instrument slot, one needs to multiply the 0-based instrument index with 128, which would in this case turn out to be **256**.

There is also a command which retrieves all instrument indices in a table. See [get_instrument_indices](#).

Constants

max_num_multi_scripts

`max_num_multi_scripts: integer`

As of Kontakt 7.5, this constant returns **5**.

Get Property

get_multi_name

```
get_multi_name() -> string
```

Returns the name of the multi.

get_multi_script_name

```
get_multi_script_name(multi_script_idx: integer) -> string
```

Returns the title of the multi script in the specified multi script slot.

get_multi_script_source

```
get_multi_script_source(multi_script_idx: integer) -> string
```

Returns the complete multi script contained in the specified multi script slot.

get_num_instruments

```
get_num_instruments() -> integer
```

Returns the number of instruments loaded in the multi.

is_multi_script_bypassed

```
is_multi_script_bypassed(multi_script_idx: integer) -> bool
```

Returns **true** if the specified multi script slot is bypassed.

is_multi_script_protected

```
is_multi_script_protected(multi_script_idx: integer) -> bool
```

Returns **true** if the specified multi script slot is protected with a password.

Set Property

set_multi_name

```
set_multi_name(name: string)
```

Sets the name of the multi.

set_multi_script_bypassed

```
set_multi_script_bypassed(script_idx: integer, bypass: bool)
```

Bypasses the specified script.

set_multi_script_name

```
set_multi_script_name(script_idx: integer, name: string)
```

Sets the name of the script. This will be displayed in the script slot header or the script tab if visible in performance view.

set_multi_script_source

```
set_multi_script_source(script_idx: integer, source: string)
```

Sets the multi script source by passing an absolute filepath as argument.

Modifiers

reset_multi

```
reset_multi()
```

Resets the whole multi to the default state.

File I/O

save_multi

```
save_multi(filename: string, options: table)
```

Save options can be defined by passing a table with one or more of the following entries:

- `mode`: [save_modes](#) (default: **"patch"**)
- `absolute_paths`: boolean (default: **false**)
- `compress_samples`: boolean (default: **false**)
- `samples_sub_dir`: string

Individual entries of this table can be omitted. In that case the default value is used.

load_multi

```
load_multi(filename: string)
```

Loads the specified multi. The whole instrument rack is reset beforehand.

5. Instrument

General Information

Instrument Structure

An instrument in Kontakt contains of groups and zones as its basic building blocks. Contrary to Creator Tools, in Kontakt Lua API zones are not hierarchically tied to groups. Instead, they are accessed individually and directly by their own separate index. A zone contains a property which links it to one and only one group. See [get_zone_group](#).

Additionally, an instrument in Kontakt also contains group triggering criteria, voice groups for managing polyphony, playback mode, MIDI input and audio output overrides, polyphonic effects and modulation.

Constants

cc64_modes

cc64_modes: table

- "midi_exclusive"
- "pedal_and_cc"
- "pedal_exclusive"

instrument_purge_modes

instrument_purge_modes: table

- "all_samples"
- "reload_all_samples"
- "reset_markers"
- "update_sample_pool"

max_num_instrument_aux

max_num_instrument_aux: integer

As of Kontakt 7.5, this constant returns **4**.

max_num_instruments

max_num_instruments: integer

As of Kontakt 7.5, this constant returns **64**.

max_num_scripts

max_num_scripts: integer

As of Kontakt 7.5, this constant returns **5**.

max_num_voice_groups

max_num_voice_groups: integer

As of Kontakt 7.5, this constant returns **128**.

save_modes

save_modes: table

- "monolith"
- "patch"
- "samples"

voice_stealing_modes

voice_stealing_modes: table

- "any"
- "highest"
- "lowest"

- "newest"
- "oldest"

Get Property

get_free_instrument_index

```
get_free_instrument_index() -> integer?
```

Returns the next available instrument index (not occupied with an already loaded instrument).

get_instrument_aux_level

```
get_instrument_aux_level(instrument_idx: integer, aux_index: integer) -> float
```

Returns the specified aux send level of the specified instrument.

get_instrument_indices

```
get_instrument_indices() -> table
```

The returned table contains the indices of all instruments. Pass these indices to functions taking `instrument_idx` as an argument.

get_instrument_midi_channel

```
get_instrument_midi_channel(instrument_idx: integer) -> integer
```

Returns the MIDI channel of the specified instrument.

get_instrument_mute

```
get_instrument_mute(instrument_idx: integer) -> bool
```

Returns the mute state of the specified instrument.

get_instrument_name

```
get_instrument_name(instrument_idx: integer) -> string
```

Returns the name of the specified instrument.

get_instrument_options

```
get_instrument_options(instrument_idx: integer) -> table
```

Returns specified instrument's options as a table with the following entries:

Instrument

- `key_switch`: integer (default: **nil**)
- `key_range_from`: integer (default: **0**)
- `key_range_to`: integer (default: **127**)
- `velocity_range_from`: integer (default: **0**)
- `velocity_range_to`: integer (default: **127**)
- `midi_transpose`: integer (default: **0**)
- `wallpaper`: string (default: **nil**)
- `komplete_ui_module_name`: string (default: **""**)
- `komplete_ui_width`: integer (default: **633**)

- `komplete_ui_height`: integer (default: **50**)

Voice Handling

- `voice_stealing_mode`: [voice_stealing_modes](#) (default: **"oldest"**)
- `voice_stealing_fadeout`: integer (default: **10**)
- `time_machine_voice_limit`: integer (default: **8**)
- `time_machine_voice_limit_hq`: integer (default: **4**)
- `time_machine_use_legacy`: boolean (default: **false**)

DFD

- `dfd_buffersize`: integer (default: **60**)
- `background_loading`: boolean (default: **true**)

Controller

- `cc_64_mode`: [cc64_modes](#) (default: **"pedal_and_cc"**)
- `use_cc_120_123`: boolean (default: **true**)
- `use_cc_7_10`: boolean (default: **true**)
- `cc_7_range`: integer (default: **0**)

Snapshots

- `show_factory_snapshots`: boolean (default: **true**)
- `factory_snapshot_path`: string (default: depends on instrument, or **nil**)
- `user_snapshot_path`: string (default: depends on instrument, or **nil**)

Info

- `info_icon`: integer (default: **28**)
- `info`: string (default: **"(null)"**)
- `info_author`: string (default: **"Kontakt"**)
- `info_url`: string (default: **"(null)"**)

Individual entries of this table can be omitted. In that case the default value is used.

get_instrument_output_channel

```
get_instrument_output_channel(instrument_idx: integer) -> integer
```

Returns the audio output channel of the specified instrument.

get_instrument_pan

```
get_instrument_pan(instrument_idx: integer) -> float
```

Returns the output panorama of the specified instrument.

get_instrument_polyphony

```
get_instrument_polyphony(instrument_idx: integer) -> integer
```

Returns the maximum polyphony of the specified instrument.

get_instrument_script_linked_filename

```
get_instrument_script_linked_filename(instrument_idx: integer, script_idx: integer)
-> string
```

Returns the filename of the script linked to the specified script slot in the specified instrument.

get_instrument_script_name

```
get_instrument_script_name(instrument_idx: integer, script_idx: integer) -> string
```

Returns the title of the script in the specified script slot in the specified instrument.

get_instrument_script_source

```
get_instrument_script_source(instrument_idx: integer, script_idx: integer) -> string
```

Returns the complete script contained in the specified script slot in the specified instrument.

get_instrument_solo

```
get_instrument_solo(instrument_idx: integer) -> bool
```

Returns the solo state of the specified instrument.

get_instrument_tune

```
get_instrument_tune(instrument_idx: integer) -> float
```

Returns the tuning of the specified instrument in semitones.

get_instrument_volume

```
get_instrument_volume(instrument_idx: integer) -> float
```

Returns the output volume of the specified instrument in dB.

get_voice_groups

```
get_voice_groups(instrument_idx: integer) -> table
```

Returns all voice groups of the specified instrument as a table with a maximum of 128 entries.

is_instrument_script_bypassed

```
is_instrument_script_bypassed(instrument_idx: integer, script_idx: integer) -> bool
```

Returns **true** if the specified script slot in the specified instrument is bypassed.

is_instrument_script_linked

```
is_instrument_script_linked(instrument_idx: integer, script_idx: integer) -> bool
```

Returns **true** if the script at the specified script slot of the specified instrument index is linked to a file in the resource container.

is_instrument_script_protected

```
is_instrument_script_protected(instrument_idx: integer, script_idx: integer) -> bool
```

Returns **true** if the specified script slot in the specified instrument is protected with a password.

Set Property

reset_instrument

```
reset_instrument(instrument_idx: integer)
```

Resets the whole instrument at the specified instrument index to the default state.

set_instrument_aux_level

```
set_instrument_aux_level(instrument_idx: integer, aux_index: integer, level: float)
```

Sets the level of the specified aux index for the specified instrument in dB. Range is **-math.huge ... 12.0**.

set_instrument_midi_channel

```
set_instrument_midi_channel(instrument_idx: integer, channel: integer)
```

Sets the MIDI channel for the specified instrument. **0** is Omni, **1 ... 64** is channels 1-16 across ports A-D.

set_instrument_mute

```
set_instrument_mute(instrument_idx: integer, value: bool)
```

Mutes the specified instrument.

set_instrument_name

```
set_instrument_name(instrument_idx: integer, name: string)
```

Sets the name of the specified instrument.

set_instrument_options

```
set_instrument_options(instrument_idx: integer, options: table)
```

Specified instrument's options can be set by passing a table with one or more of the following entries:

Instrument

- **key_switch**: integer (default: **nil**)
- **key_range_from**: integer (default: **0**)
- **key_range_to**: integer (default: **127**)
- **velocity_range_from**: integer (default: **0**)
- **velocity_range_to**: integer (default: **127**)
- **midi_transpose**: integer (default: **0**)
- **wallpaper**: string (default: **nil**)

- `komplete_ui_module_name`: string (default: `""`)

A module name is simply the file's name without the `kscript` file extension. If you want to set a module nested in one or more folders, you need to separate the folder names with a dot (`.`). Given the following project structure:

```
komplete_scripts/
  one.kscript
  folder/
    two.kscript
```

If you want `one.kscript` to be the main module you would set `"one"`. If you would want to load `two.kscript` you'd set `"folder.two"`

- `komplete_ui_width`: integer (default: **633**)
The width needs to be between **633** and **1000**.
- `komplete_ui_height`: integer (default: **50**)
The height needs to be between **50** and **750**.

Voice Handling

- `voice_stealing_mode`: [voice_stealing_modes](#) (default: `"oldest"`)
- `voice_stealing_fadeout`: integer (default: **10**)
- `time_machine_voice_limit`: integer (default: **8**)
- `time_machine_voice_limit_hq`: integer (default: **4**)
- `time_machine_use_legacy`: boolean (default: **false**)

DFD

- `dfd_buffersize`: integer (default: **60**)
- `background_loading`: boolean (default: **true**)

Controller

- `cc_64_mode`: [cc64_modes](#) (default: `"pedal_and_cc"`)
- `use_cc_120_123`: boolean (default: **true**)
- `use_cc_7_10`: boolean (default: **true**)
- `cc_7_range`: integer (default: **0**)

Snapshots

- `show_factory_snapshots`: boolean (default: **true**)
- `factory_snapshot_path`: string (default: depends on instrument, or **nil**)
- `user_snapshot_path`: string (default: depends on instrument, or **nil**)

Info

- `info_icon`: integer (default: **28**)
- `info`: string (default: `"(null)"`)
- `info_author`: string (default: `"Kontakt"`)
- `info_url`: string (default: `"(null)"`)

Individual entries of this table can be omitted. In that case the default value is used.

set_instrument_output_channel

```
set_instrument_output_channel(instrument_idx: integer, channel: integer)
```

Sets the audio output for the specified instrument. Make sure to check how many outputs are available before setting!

set_instrument_pan

```
set_instrument_pan(instrument_idx: integer, percent: float)
```

Sets the output panorama of the specified instrument. Range is **-100.0 ... 100.0**.

set_instrument_polyphony

```
set_instrument_polyphony(instrument_idx: integer, voices: integer)
```

Sets the maximum polyphony for the specified instrument. Minimum value is **1**.

set_instrument_script_bypassed

```
set_instrument_script_bypassed(instrument_idx: integer, script_idx: integer,  
bypass: bool)
```

Bypasses the specified script of the specified instrument.

set_instrument_script_linked_filename

```
set_instrument_script_linked_filename(instrument_idx: integer, script_idx: integer,  
filename: string)
```

Sets the filename of the script packed inside the resource container and linked to a script slot.

set_instrument_script_name

```
set_instrument_script_name(instrument_idx: integer, script_idx: integer, name:  
string)
```

Sets the name of the script (without extension). This will be displayed in the script slot header or the script tab if visible in performance view.

set_instrument_script_source

```
set_instrument_script_source(instrument_idx: integer, script_idx: integer, source:  
string)
```

Sets the script source by passing an absolute filepath as argument.

set_instrument_solo

```
set_instrument_solo(instrument_idx: integer, value: bool)
```

Soloes the specified instrument.

set_instrument_tune

```
set_instrument_tune(instrument_idx: integer, semitones: float)
```

Sets the output tuning of the specified instrument in semitones. Range is **-36.0 ... 36.0**.

set_instrument_volume

```
set_instrument_volume(instrument_idx: integer, level: float)
```

Sets the output volume of the specified instrument in dB. Range is **-math.huge ... 12.0**.

set_voice_groups

```
set_voice_groups(instrument_idx: integer, voice_groups: table)
```

Sets voice groups of the specified instrument as a table with a maximum of 128 entries, matching the total number of possible voice groups. Nil table entries will set voice group to default values.

Voice group parameters are defined in a sub-table:

- **mode:** [voice_group_modes](#) (default: **"oldest"**)
- **name:** string (default: **"**)
- **voices:** integer (default: **1**)
- **fade_time:** integer (default: **10**)
- **prefer_released:** boolean (default: **true**)
- **exclusive_group:** integer (default: **nil**)

Individual entries of this table can be omitted. In that case the default value is used.

Modifiers

add_instrument

```
add_instrument(instrument_idx: integer?) -> integer
```

Inserts a new instrument at given or next available instrument index. Returns the index of the new instrument. Pass this index to functions taking `instrument_idx` as an argument.

add_instrument_bank

```
add_instrument_bank(instrument_slot: integer?) -> integer
```

Inserts a new instrument bank at given or next available instrument slot. Returns the instrument slot of the new instrument bank.

remove_instrument

```
remove_instrument(instrument_idx: integer)
```

Removes the instrument at the specified instrument index from the multi.

remove_instrument_bank

```
remove_instrument_bank(instrument_slot: integer)
```

Removes the instrument bank at the specified instrument slot from the multi.

File I/O

load_instrument

```
load_instrument(filename: string, instrument_idx: integer?) -> integer
```

Loads an instrument to the specified slot index. If that slot is already occupied, next available slot is used. Returns the slot index of the new instrument. **Note:** contrary to most other functions, the slot index here can also refer to a slot within an instrument bank!

load_snapshot

```
load_snapshot(instrument_idx: integer, filename: string)
```

Loads the specified snapshot in the specified instrument index.

save_instrument

```
save_instrument(instrument_idx: integer, filename: string, options: table)
```

Save options can be defined by passing a table with one or more of the following entries:

- mode: [save_modes](#) (default: **"patch"**)
- absolute_paths: boolean (default: **false**)
- compress_samples: boolean (default: **false**)
- samples_sub_dir: string

Individual entries of this table can be omitted. In that case the default value is used.

save_snapshot

```
save_snapshot(instrument_idx: integer, filename: string)
```

Saves the state of the instrument at the specified instrument index as a snapshot at the specified absolute path.

6. Group

Constants

group_playback_modes

group_playback_modes: table

- "beat_machine"
- "dfd"
- "mpc60_machine"
- "s1200_machine"
- "sampler"
- "time_machine_1"
- "time_machine_2"
- "time_machine_pro"
- "tone_machine"
- "wavetable"

group_start_conditions

group_start_conditions: table

- "controller"
- "key"
- "random"
- "round_robin"
- "slice_trigger"

group_start_operators

group_start_operators: table

- "and"
- "and_not"
- "or"

max_num_group_start_criteria

max_num_group_start_criteria: integer

As of Kontakt 7.5, this constant returns **4**.

max_num_groups

max_num_groups: integer

As of Kontakt 7.5, this constant returns **4096**.

voice_group_modes

voice_group_modes: table

- "any"

- "highest"
- "lowest"
- "newest"
- "oldest"

Get Property

get_group_name

```
get_group_name(instrument_idx: integer, group_idx: integer) -> string
```

Returns the name of the specified group.

get_group_pan

```
get_group_pan(instrument_idx: integer, group_idx: integer) -> float
```

Returns the amplifier panorama of the specified group.

get_group_playback_mode

```
get_group_playback_mode(instrument_idx: integer, group_idx: integer) -> string
```

Returns the playback mode of the specified group's Source module. See [group_playback_modes](#).

get_group_start_options

```
get_group_start_options(instrument_idx: integer, group_idx: integer) -> table
```

Returns specified group's start options as a table with a maximum of 4 sub-tables:

A certain group start option condition can be defined by passing a table. This table has different entries based on condition type:

Start On Key

- mode: "key"
- key_min: integer (default: **24**)
- key_max: integer (default: **24**)
- next: [group_start_operators](#) (default: "and")

Start On Controller

- mode: "controller"
- controller: (default: **1**)
- cc_min: (default: **0**)
- cc_max: (default: **64**)
- next: [group_start_operators](#) (default: "and")

Cycle Round Robin

- mode: "round_robin"
- position: integer (default: **1**)
- next: [group_start_operators](#) (default: "and")

Cycle Random

- mode: "random"
- next: [group_start_operators](#) (default: "and")

Slice Trigger

- mode: "slice_trigger"
- zone: integer (default: **nil**)

- `slice`: integer (default: **nil**)
- `internal`: boolean (default: **false**)
- `next`: [group_start_operators](#) (default: **"and"**)

Individual entries of this table can be omitted. In that case the default value is used. See also: [group_start_conditions](#)

get_group_tune

```
get_group_tune(instrument_idx: integer, group_idx: integer) -> float
```

Returns the tuning of the specified group in semitones.

get_group_volume

```
get_group_volume(instrument_idx: integer, group_idx: integer) -> float
```

Returns the amplifier volume of the specified group in dB.

get_num_groups

```
get_num_groups(instrument_idx: integer) -> integer
```

Returns the total number of groups in the specified instrument.

get_voice_group

```
get_voice_group(instrument_idx: integer, group_idx: integer) -> integer?
```

Returns the voice group assigned to a group. If no voice group is assigned, the returned value is **nil**.

Set Property

set_group_name

```
set_group_name(instrument_idx: integer, group_idx: integer, name: string)
```

Sets the name of the specified group.

set_group_pan

```
set_group_pan(instrument_idx: integer, group_idx: integer, pan: float)
```

Sets the amplifier panorama of the specified group. Range is **-100.0 ... 100.0**.

set_group_playback_mode

```
set_group_playback_mode(instrument_idx: integer, group_idx: integer, mode: string)
```

Sets the playback mode of the specified group's Source module. See [group_playback_modes](#).

set_group_start_options

```
set_group_start_options(instrument_idx: integer, group_idx: integer, options: table)
```

Start On Key

- mode: "key"
- key_min: integer (default: **24**)
- key_max: integer (default: **24**)
- next: [group_start_operators](#) (default: "and")

Start On Controller

- mode: "controller"
- controller: (default: **1**)
- cc_min: (default: **0**)
- cc_max: (default: **64**)
- next: [group_start_operators](#) (default: "and")

Cycle Round Robin

- mode: "round_robin"
- position: integer (default: **1**)
- next: [group_start_operators](#) (default: "and")

Cycle Random

- mode: "random"
- next: [group_start_operators](#) (default: "and")

Slice Trigger

- mode: "slice_trigger"
- zone: integer (default: **nil**)
- slice: integer (default: **nil**)
- internal: boolean (default: **false**)
- next: [group_start_operators](#) (default: "and")

Individual entries of this table can be omitted. In that case the default value is used. See also: [group_start_conditions](#)

set_group_tune

```
set_group_tune(instrument_idx: integer, group_idx: integer, tune: float)
```

Sets the tuning of the specified group in semitones. Range is **-36.0 ... 36.0**.

set_group_volume

```
set_group_volume(instrument_idx: integer, group_idx: integer, volume: float)
```

Sets the amplifier volume of the specified group in dB. Range is **-math.huge ... 12.0**.

set_voice_group

```
set_voice_group(instrument_idx: integer, group_idx: integer, voice_group: integer)
```

Assign a voice group to a group. In order to reset the assignment pass **nil**.

Modifiers

add_group

```
add_group(instrument_idx: integer) -> integer
```

Returns the index of the new group. Pass this index to functions taking **group_idx** as an argument.

remove_group

```
remove_group(instrument_idx: integer, group_idx: integer) -> bool
```

Removes the specified group from the specified instrument.

File I/O

load_group

```
load_group(instrument_idx: integer, group_idx: integer, filename: string, options: table)
```

Options table currently has a single entry:

- `replace_zones`: boolean (default: **false**)

save_group

```
save_group(instrument_idx: integer, group_idx: integer, filename: string, options: table)
```

Save options can be defined by passing a table with one or more of the following entries:

- `mode`: [save_modes](#) (default: **"patch"**)
- `absolute_paths`: boolean (default: **false**)
- `compress_samples`: boolean (default: **false**)
- `samples_sub_dir`: string

Individual entries of this table can be omitted. In that case the default value is used.

7. Zone

Constants

max_num_sample_loops

max_num_sample_loops: integer

As of Kontakt 7.5, this constant returns **8**.

max_num_zones

max_num_zones: integer

As of Kontakt 7.5, this constant returns **98304**.

sample_loop_modes

sample_loop_modes: table

- "off"
- "until_end"
- "until_end_alt"
- "until_release"
- "until_release_alt"

zone_grid_modes

zone_grid_modes: table

- "auto"
- "fixed"
- "none"

Get Property

get_num_zones

```
get_num_zones(instrument_idx: integer) -> integer
```

Returns the total number of zones in the specified instrument.

get_sample_loop_count

```
get_sample_loop_count(instrument_idx: integer, zone_idx: integer, loop_idx: integer) -> integer
```

Returns the loop count of the specified zone's loop.

get_sample_loop_length

```
get_sample_loop_length(instrument_idx: integer, zone_idx: integer, loop_idx: integer) -> integer
```

Returns the loop length of the specified zone's loop.

get_sample_loop_mode

```
get_sample_loop_mode(instrument_idx: integer, zone_idx: integer, loop_idx: integer) -> string
```

Returns the loop mode of the specified zone's loop. See [sample_loop_modes](#).

get_sample_loop_start

```
get_sample_loop_start(instrument_idx: integer, zone_idx: integer, loop_idx: integer) -> integer
```

Returns the loop start of the specified zone's loop.

get_sample_loop_tune

```
get_sample_loop_tune(instrument_idx: integer, zone_idx: integer, loop_idx: integer) -> float
```

Returns the loop tuning of the specified zone's loop in semitones.

get_sample_loop_xfade

```
get_sample_loop_xfade(instrument_idx: integer, zone_idx: integer, loop_idx: integer) -> integer
```

Returns the loop crossfade time of the specified zone's loop.

get_zone_geometry

```
get_zone_geometry(instrument_idx: integer, zone_idx: integer) -> table
```

Returns a table containing the complete zone geometry (key and velocity ranges, root key, zone crossfades, etc.). See [set_zone_geometry](#).

get_zone_grid_bpm

```
get_zone_grid_bpm(instrument_idx: integer, zone_idx: integer) -> float
```

Returns the BPM of the specified zone.

get_zone_grid_mode

```
get_zone_grid_mode(instrument_idx: integer, zone_idx: integer) -> string
```

Returns the grid mode of the specified zone. See [zone_grid_modes](#).

get_zone_group

```
get_zone_group(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the index of the group which contains the specified zone.

get_zone_high_key

```
get_zone_high_key(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the high key of the specified zone.

get_zone_high_key_fade

```
get_zone_high_key_fade(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the high key crossfade span of the specified zone.

get_zone_high_velocity

```
get_zone_high_velocity(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the high velocity of the specified zone.

get_zone_high_velocity_fade

```
get_zone_high_velocity_fade(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the high velocity crossfade span of the specified zone.

get_zone_low_key

```
get_zone_low_key(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the low key of the specified zone.

get_zone_low_key_fade

```
get_zone_low_key_fade(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the low key crossfade span of the specified zone.

get_zone_low_velocity

```
get_zone_low_velocity(instrument_idx: integer, zone_idx: integer) -> float
```

Returns the low velocity of the specified zone.

get_zone_low_velocity_fade

```
get_zone_low_velocity_fade(instrument_idx: integer, zone_idx: integer) -> float
```

Returns the low velocity crossfade span of the specified zone.

get_zone_pan

```
get_zone_pan(instrument_idx: integer, group_idx: integer) -> float
```

Returns the panorama offset of the specified zone.

get_zone_root_key

```
get_zone_root_key(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the root key of the specified zone.

get_zone_sample

```
get_zone_sample(instrument_idx: integer, zone_idx: integer) -> string?
```

Returns the absolute file path of the sample loaded in the specified zone.

get_zone_sample_channels

```
get_zone_sample_channels(instrument_idx: integer, zone_idx: integer) -> integer?
```

Returns the number of audio channels in the sample loaded in the specified zone.

get_zone_sample_end

```
get_zone_sample_end(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the sample end position for the specified zone. This is expressed in negative frames, by how far away the sample end marker is from last sample frame, so in order to get the same value as displayed in Kontakt's Wave Editor, use `get_zone_sample_frames() + get_zone_sample_end()`.

get_zone_sample_frames

```
get_zone_sample_frames(instrument_idx: integer, zone_idx: integer) -> integer?
```

Returns the length of the sample loaded in the specified zone.

get_zone_sample_start

```
get_zone_sample_start(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the sample start position for the specified zone.

get_zone_sample_start_mod_range

```
get_zone_sample_start_mod_range(instrument_idx: integer, zone_idx: integer) -> integer
```

Returns the sample start modulation range for the specified zone.

get_zone_tune

```
get_zone_tune(instrument_idx: integer, zone_idx: integer) -> float
```

Returns the tuning offset of the specified zone in semitones.

get_zone_volume

```
get_zone_volume(instrument_idx: integer, zone_idx: integer) -> float
```

Returns the volume offset of the specified zone in dB.

Set Property

set_sample_loop_count

```
set_sample_loop_count(instrument_idx: integer, zone_idx: integer, loop_idx: integer, count: integer)
```

Sets the loop count of the specified zone's loop.

set_sample_loop_length

```
set_sample_loop_length(instrument_idx: integer, zone_idx: integer, loop_idx: integer, frames: integer)
```

Sets the length for the specified zone's loop in sample frames.

set_sample_loop_mode

```
set_sample_loop_mode(instrument_idx: integer, zone_idx: integer, loop_idx: integer, mode: string)
```

Sets the playback mode for the specified zone's loop. See [sample_loop_modes](#).

set_sample_loop_start

```
set_sample_loop_start(instrument_idx: integer, zone_idx: integer, loop_idx: integer, frame: integer)
```

Sets the start of the specified zone's loop.

set_sample_loop_tune

```
set_sample_loop_tune(instrument_idx: integer, zone_idx: integer, loop_idx: integer, tune: float)
```

Sets the tuning of the specified zone's loop in semitones. Range is **-12.0 ... 12.0**.

set_sample_loop_xfade

```
set_sample_loop_xfade(instrument_idx: integer, zone_idx: integer, loop_idx: integer, frames: integer)
```

Sets the length of the specified zone's loop xfade in sample frames.

set_zone_geometry

```
set_zone_geometry(instrument_idx: integer, zone_idx: integer, geometry: table)
```

Applies **geometry** to the specified zone. This consists of a table of the following properties which specify the boundaries of the zone.

Geometry:

- **root_key** (default: **36**, range: **0 ... 127**)
- **low_key** (default: **0**, range: **0 ... high_key**)
- **high_key** (default: **127**, range: **low_key ... 127**)
- **low_key_fade** (default: **0**, range: **0 ... span**)
- **high_key_fade** (default: **0**, range: **0 ... span**)

- `low_velocity` (default: **1**, range: **1** ... **high_velocity**)
- `high_velocity` (default: **127**, range: **low_velocity** ... **127**)
- `low_velocity_fade` (default: **0**, range: **0** ... **span**)
- `high_velocity_fade` (default: **0**, range: **0** ... **span**)

`span` is defined as: $\text{high_key} / \text{velocity} + 1 - \text{low_key} / \text{velocity} - \text{opposite_fade_value}$. So if setting `low_key_fade`, use the value of `high_key_fade` as `opposite_fade_value`

set_zone_grid

```
set_zone_grid(instrument_idx: integer, zone_idx: integer, mode: string, bpm: float)
```

Sets the grid of the specified zone. See [zone_grid_modes](#).

set_zone_group

```
set_zone_group(instrument_idx: integer, zone_idx: integer, group_idx: integer)
```

Sets the group index for the specified zone. This effectively moves the zone to the specified group without the need for creating a new zone and copying zone properties.

set_zone_high_key

```
set_zone_high_key(instrument_idx: integer, zone_idx: integer, key: integer)
```

See [set_zone_geometry](#).

set_zone_high_key_fade

```
set_zone_high_key_fade(instrument_idx: integer, zone_idx: integer, key_fade: integer)
```

See [set_zone_geometry](#).

set_zone_high_velocity

```
set_zone_high_velocity(instrument_idx: integer, zone_idx: integer, velocity: integer)
```

See [set_zone_geometry](#).

set_zone_high_velocity_fade

```
set_zone_high_velocity_fade(instrument_idx: integer, zone_idx: integer, velocity_fade: integer)
```

See [set_zone_geometry](#).

set_zone_low_key

```
set_zone_low_key(instrument_idx: integer, zone_idx: integer, key: integer)
```

See [set_zone_geometry](#).

set_zone_low_key_fade

```
set_zone_low_key_fade(instrument_idx: integer, zone_idx: integer, key_fade: integer)
```

See [set_zone_geometry](#).

set_zone_low_velocity

```
set_zone_low_velocity(instrument_idx: integer, zone_idx: integer, velocity: integer)
```

See [set_zone_geometry](#).

set_zone_low_velocity_fade

```
set_zone_low_velocity_fade(instrument_idx: integer, zone_idx: integer,
velocity_fade: integer)
```

See [set_zone_geometry](#).

set_zone_pan

```
set_zone_pan(instrument_idx: integer, zone_idx: integer, pan: float)
```

Sets the panorama offset of the specified zone. Range is **-100.0 ... 100.0**.

set_zone_root_key

```
set_zone_root_key(instrument_idx: integer, zone_idx: integer, key: integer)
```

See [set_zone_geometry](#).

set_zone_sample

```
set_zone_sample(instrument_idx: integer, zone_idx: integer, filename: string)
```

Sets the absolute path of the sample to be loaded in the specified zone.

set_zone_sample_end

```
set_zone_sample_end(instrument_idx: integer, zone_idx: integer, frame: integer)
```

Sets the sample end of the sample loaded in the specified zone. This is expressed in negative frames, by how far away the sample end marker is from last sample frame.

set_zone_sample_start

```
set_zone_sample_start(instrument_idx: integer, zone_idx: integer, frame: integer)
```

Sets the sample start of the sample loaded in the specified zone, in sample frames.

set_zone_sample_start_mod_range

```
set_zone_sample_start_mod_range(instrument_idx: integer, zone_idx: integer, frame:
integer)
```

Sets the sample start modulation range of the sample loaded in the specified zone, in sample frames.

set_zone_tune

```
set_zone_tune(instrument_idx: integer, zone_idx: integer, tune: float)
```

Sets the tuning offset of the specified zone in semitones. Range is **-36.0 ... 36.0**.

set_zone_volume

```
set_zone_volume(instrument_idx: integer, zone_idx: integer, volume: float)
```

Sets the volume offset of the specified zone in dB. Range is **-36.0** ... **36.0**.

Modifiers

add_zone

```
add_zone(instrument_idx: integer, group_idx: integer, filename: string) -> integer
```

The returned index refers the added zone. Pass this index to functions taking `zone_idx` as an argument.

remove_zone

```
remove_zone(instrument_idx: integer, zone_idx: integer)
```

Removes the specified zone index from the instrument at the specified instrument index.

restore_loops_from_sample

```
restore_loops_from_sample(instrument_idx: integer, zone_idx: integer)
```

Sets the loop points to the values stored in the sample metadata, if it exists.

8. Presets

Constants

bus_fx

`bus_fx: integer`

Points a preset loading function to the first instrument bus FX chain. To reach other instrument buses, add a constant from **1** to **15**.

group_fx

`group_fx: integer`

Points a preset loading function to the group FX chain.

insert_fx

`insert_fx: integer`

Points a preset loading function to the insert FX chain.

main_fx

`main_fx: integer`

Points a preset loading function to the main FX chain.

output_fx

`output_fx: integer`

Points a preset loading function to the output FX chain. Does not apply to `load_fx_chain_preset()`.

send_fx

`send_fx: integer`

Points a preset loading function to the send FX chain.

File I/O

load_source_preset

```
load_source_preset(filename: string, instrument_idx: integer, group_idx: integer)
-> integer
```

Loads a source preset file (.NKP) to the specified group of an instrument.

load_fx_preset

```
load_fx_preset(filename: string, instrument_or_output_idx: integer, group_idx:
integer, generic: integer) -> integer
```

Loads an effect preset file (.NKP) to the specified location based on the following arguments:

- **instrument_or_output**: if **generic** argument is **output_fx**, this is one of output channels in the Output panel (**0 ... 127**), else it's an instrument index
- **group**: only valid when **generic** argument is **group_fx**, else set to **-1**
- **slot**: index of the slot to which the effect preset should be loaded
- **generic**: use one of FX chain location constants (**group_fx**, **send_fx**, etc.)

load_multi_script_preset

```
load_multi_script_preset(filename: string, instrument_idx: integer,
multi_script_idx: integer) -> integer
```

Loads a multi script preset file (.NKP) to the specified multi script slot.

load_script_preset

```
load_script_preset(filename: string, instrument_idx: integer, script_idx: integer)
-> integer
```

Loads a script preset file (.NKP) to the specified script slot of an instrument.

load_fx_chain_preset

```
load_fx_chain_preset(filename: string, instrument_idx: integer, group_idx: integer,
generic: integer) -> integer
```

Loads a complete effect chain preset file (.NKP) to the specified location based on the following arguments:

- **instrument**: instrument index
- **group**: only valid when **generic** argument is **group_fx**, else set to **-1**
- **generic**: use one of FX chain location constants, except **output_fx**

9. Options

Constants

desktop_path

`desktop_path: string`

Returns the absolute path to operating system's Desktop folder.

documents_path

`documents_path: string`

Returns the absolute path to operating system's Documents folder.

factory_path

`factory_path: string`

Returns the Kontakt factory data path (contains wavetables, NKP presets, and so on).

macos

`macos: bool`

Returns **true** if the system running the Lua script is macOS.

ni_content_path

`ni_content_path: string`

Returns the absolute path to NI Content folder.

non_player_content_base_path

`non_player_content_base_path: string`

Returns the non-Player content base path (which is optionally set in Kontakt's *Options > Loading* pane).

snapshot_path

`snapshot_path: string`

Returns the User Content data path, which contains snapshots saved by the user.

windows

`windows: bool`

Returns **true** if the system running the Lua script is Windows.

10. Utility

Constants

colored_output

`colored_output: bool`

Controls if terminal output is colored or not.

edit_instrument

`edit_instrument: integer | nil`

Index of the currently edited instrument.

script_executed_from_instrument

`script_executed_from_instrument: integer | nil`

Index of the instrument slot from which the script was loaded. **nil** is multi.

script_file

`script_file: string`

Returns filename of the currently running Lua script, including the extension.

script_path

`script_path: string`

Returns the absolute path to the folder containing the currently running Lua script.

version

`version: string`

Returns the current version of the running instance of Kontakt.

Functions

assert_fail

```
assert_fail(test: function)
```

Unit test helper function. Calls `test` expecting it to fail. Raises an error if that does not happen.

create_resource_container

```
create_resource_container(instrument_idx: integer, filename: string)
```

Creates a new resource container (with the obligatory Resources folder) or updates an existing resource container. If the `.nkr` extension is not a part of the filename string, it will be added automatically.

link_resource_container

```
link_resource_container(instrument_idx: integer, filename: string)
```

Links an existing resource container to the instrument. If the `.nkr` extension is not a part of the filename string, it will be added automatically. Note that this command does not require the Resources folder to exist.

get_file_info

```
get_file_info(filename: string) -> table
```

Extracts information from an instrument on disk. The returned table contains the fields: `file`, `format`, `version`, `library`, `num_instruments`, `num_groups`, `num_zones`.

instrument_purge

```
instrument_purge(instrument_idx: integer, mode: string)
```

Runs one of available purge actions for the specified instrument. See [instrument_purge_modes](#).

File I/O

ncw_decode

```
ncw_decode(source: string, target: string)
```

Decodes an NCW sample back to uncompressed WAV format.

ncw_encode

```
ncw_encode(source: string, target: string)
```

Encodes a WAV or AIFF sample to losslessly compressed NCW format.

11. Filesystem

The Lua binding is based on the C++ library [boost filesystem](#). In contrary to the original C++ design, the Lua binding does not define an abstraction for path. Instead, path always refers to a Lua string. The join function allows concatenating paths using the platform dependent separator.

```
local fs = Filesystem

local script = fs.join(Kontakt.script_path, Kontakt.script_file)
assert(fs.exists(script))
```

API Access

The Filesystem API is defined in the global table **Filesystem**, i.e. all constants and functions need to be prefixed with that name. For example.

```
print(Filesystem.exists(Kontakt.script_path))

-- also works
kt = Kontakt
fs = Filesystem

print(fs.exists(kt.script_path))
```

Iterators

directory

`directory(path: string) -> iterator`

Example: lists paths in directory

```
for _, p in Filesystem.directory(path) do
    print(p)
end
```

recursive_directory

`recursive_directory(path: string) -> iterator`

Example: lists paths in directory and all sub-directories

```
for _, p in Filesystem.recursive_directory(path) do
    print(p)
end
```

Path Functions

empty

```
empty(path: string) -> boolean
```

extension

```
extension(path: string) -> string
```

filename

```
filename(path: string) -> string
```

has_parent_path

```
has_parent_path(path: string) -> boolean
```

has_relative_path

```
has_relative_path(path: string) -> boolean
```

has_root_directory

```
has_root_directory(path: string) -> boolean
```

has_extension

```
has_extension(path: string) -> boolean
```

has_filename

```
has_filename(path: string) -> boolean
```

has_root_name

```
has_root_name(path: string) -> boolean
```

is_dot_dot

```
is_dot_dot(path: string) -> boolean
```

is_dot

```
is_dot(path: string) -> boolean
```

join

```
join(paths ... : string) -> string
```

has_stem

```
has_stem(path: string) -> boolean
```

is_absolute

```
is_absolute(path: string) -> boolean
```

relative_path

```
relative_path(path: string) -> string
```

has_root_path

```
has_root_path(path: string) -> boolean
```

root_name

```
root_name(path: string) -> string
```

root_directory

```
root_directory(path: string) -> string
```

is_relative

```
is_relative(path: string) -> boolean
```

parent_path

```
parent_path(path: string) -> string
```

root_path

```
root_path(path: string) -> string
```

replace_extension

```
replace_extension(path: string, extension: string) -> string
```

preferred

```
preferred(path: string) -> string
```

stem

```
stem(path: string) -> string
```

12. Music Information Retrieval (MIR)

Music Information Retrieval is the science of retrieving information from music. Among others, it allows the extraction of meaningful features from audio files, such as the pitch or the loudness of a sample. Kontakt comes with a collection of MIR functions, to assist or automate parts of the instrument creation process.

Single functions retrieve information from single files and take as argument an absolute filename (the full path to the sample file).

API Access

The MIR API is defined in the global table **MIR**, i.e. all constants and functions need to be prefixed with that name. For example:

```
kt = Kontakt
fs = Filesystem

print(MIR.detect_pitch(fs.join(kt.script_path, 'samples/Sine440_1sec.wav')))
```

Pitch Detection

The pitch detection tries to detect the fundamental frequency of a monophonic/single note sample. It corresponds to the MIDI scale (69 = 440 Hz) and ranges from semitone 15 (~20Hz) to semitone 120 (~8.4 kHz).

detect_pitch

```
detect_pitch(file: string) -> float?
```

Analyzes **file** and returns the detected MIDI pitch or **nil** if detection fails.

Peak, RMS & Loudness detection

Loudness, Peak, and RMS functions return a value in dB, with a maximum at 0dB.

The RMS and Loudness functions are calculated over small blocks of audio. The duration of those blocks is called frame size and is expressed in seconds. The process is repeated in intervals equal to the hop size (also expressed in seconds), until it reaches the end of the sample. The functions return the overall loudest/highest value of the different blocks.

If frame size and hop size are not indicated, the default values 0.4 (frame size in seconds) and 0.1 (hop size in seconds) are applied respectively.

detect_peak

```
detect_peak(file: string) -> float?
```

Analyzes **file** and returns the detected peak level or **nil** if detection fails.

detect_rms

```
detect_rms(file: string) -> float?
```

```
detect_rms(file: string, frame_size: float, hop_size: float) -> float?
```

Analyzes **file** and returns the detected RMS level or **nil** if detection fails.

detect_loudness

```
detect_loudness(file: string) -> float?
```

```
detect_loudness(file: string, frame_size: float, hop_size: float) -> float?
```

Analyzes **file** and returns the detected loudness level or **nil** if the detection fails.

Loop Detection

```
find_loop(file: string) -> start: integer?, end: integer?  
find_loop(file: string, min_start: float, max_end: float, min_length: float) ->  
start: integer?, end: integer?
```

Analyzes **file** and returns the detected loop points or **nil** if detection fails.

Type Detection

Type detection is a means to determine which category a given audio sample belongs to. Currently, Kontakt Lua API supports detection of three distinct types: Sample Type, Drum Type, and Instrument Type. Sample Type is used to determine if a sample is either a drum or an instrument. Drum Type and Instrument Type both determine which drum or instrument category a sample belongs to.

sample_type

```
detect_sample_type(file: string) -> string
```

Returns the sample type of **file**. Returns one of the following types or **nil** if detection fails:

- *drum*
- *instrument*

detect_drum_type

```
detect_drum_type(file: string) -> string
```

Returns the drum type of **file**. Returns one of the following types or **nil** if detection failed.

- *kick*
- *snare*
- *hihat_closed*
- *hihat_open*
- *tom*
- *cymbal*
- *clap*
- *shaker*
- *percussion_drum*
- *percussion_other*

detect_instrument_type

```
detect_instrument_type(file: string) -> string
```

Returns the instrument type of **file**. Return one of the following types or **nil** if detection fails.

- *bass*
- *bowed_string*
- *brass*
- *flute*
- *guitar*
- *keyboard*
- *mallet*
- *organ*
- *plucked_string*
- *reed*
- *synth*
- *vocal*

13. Version History

Kontakt 8.2

New Features

- Added `set_komplete_ui_module`
- Added `get_komplete_ui_module`
- Added `set_komplete_ui_size`
- Added `get_komplete_ui_size`

Fixes

- Fixed `get_instrument_options` and `set_instrument_options` didn't work with encoded instruments

Kontakt 8.1

New Features

- Added `set_zone_group()` command.

Kontakt 8

New Features

- Added `factory_snapshot_path` and `user_snapshot_path` entries to the [Instrument Options table](#).

Fixes

- `set_group_start_options()` did not respect the given group index, it was always applied to all selected groups instead.

Kontakt 7.10.7

New Features

- Added `factory_snapshot_path` and `user_snapshot_path` entries to the [Instrument Options table](#).

Fixes

- `set_group_start_options()` did not respect the given group index, it was always applied to all selected groups instead.

Kontakt 7.8

New Features

- `link_resource_container()` command.

Improved Features

- When creating a resource container, typing `.nkr` extension is not required anymore.
- When drag and dropping a Lua script onto Kontakt's rack, it will now be listed in recently used scripts.
- If there is an error when creating a resource container, dialog will not be created any longer, instead this information will be logged to the terminal.

Fixes

- When creating a resource container, scripts from **Resources/scripts** folder would not be available to the builder for linking immediately.
- When linking a script via `set_instrument_script_linked_filename()`, the script would not be applied.